

PRODUCT INFORMATION

Washfit NVC af hp 2326

VOC-free wash for manual and automatic cleaning in coldset and sheetfed

FIELD OF APPLICATION

- Low consumption
- Minimal consumption
- Fast washing process
- Low odour

- Not classified as "hazardous" for transport
- · Low risk of web breaks in web applications
- Short washing time
- Intensively removes ink and paper build up

PROPERTIES

- · For rollers and blankets
- For conventional inks
- For NBR materials
- Corrosion inhibited

- Non-VOC
- Slow evaporation
- Spontaneous emulsion with water
- · Outstanding ink solvency power

APPLICATION -

Blankets: Apply with a cloth or lint free wipe to the blanket. Allow a few seconds for wash to penetrate the ink film, then wipe over with a clean cloth or wipe. Finally rinse surface with clean water.

Rollers: Apply with a wash bottle and run into the roller train. Apply scraper blade to remove ink/wash mixture. Finally wash with clean water.

Automatic washing systems: Fill and adjust the wash system in accordance with press manufacturer's instructions. Ensure sufficient water is used in the wash up cycle to ensure complete removal of wash residues.

SPECIFICATIONS

- Flashpoint (°C): >100 <0,1
- Aromatic content (%):

VOC free

CORRESPONDING PRODUCTS

Extrafit Wash Wateradditive	Corrosion inhibited additive for washing units for optimum cleaning performance
Extrafit Roller Gel	Calcium cleaning gel with excellent cleaning power
Waterfit	Fountain solution for maximum productivity due to stable process
Extrafit Damp Cleaner	Highly efficient cleaner for side frames, machine parts and floors

STANDARD PACKAGING

• 20 LTR • 200 LTR • 1.000 LTR

Note: This technical description is intended to inform and advise you. It corresponds to our current state of knowledge. However, since the specific application depends on a number of factors over which we have no influence, no guarantee and liability for the pressure failure can be derived.

> Epple Druckfarben AG Gutenbergstr. 5 . 86356 Neusäß . Germany . Tel. +49 821 4603 0 . Fax +49 821 4603 200 . info@epple-druckfarben.de Mehr Informationen finden Sie unter: www.epple-druckfarben.de